



Submerged | 220-240 V | 1 x powerLEDs 0,5 W 230 V | RGB
15158



Technical data	
Type	Submerged
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Power	0.5 W
Frequency	60 - 50 Hz
CCT / Tone	RGB
AC / DC	DC
Safety class	2
IP	IP68
IK	IK10
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Driver included	Driver
Induction	Yes
Min duration	12 h
Max duration	14.5 h
Charging time	6 h
Emergency mode	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1.180 Kg

Finishing diffuser	
Material	PE
Colour	neutral



Submerged | 220-240 V | 1 x powerLEDs 0,5 W 230 V | RGB
15158

Single emission floor lamp for outdoor application. The RGB LED light source with a general lighting light distribution is composed of 1.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP68; the total weight is of 1.180 kg.

The total absorbed power is 0,5 W.

The device features protection class II and can be floor-mounted.