




Ceiling Lights | 220-240 V | 1xE27
15189



Ø 1150

| Technical data | |
|--|------------------|
| Type | Surface |
| Installation position | Ceiling |
| Installation environment | Outdoor |
| Lamp cap | 1 x E27 Max 77W |
| Frequency | 50-60 Hz |
| Optics | General Lighting |
| Safety class | 2 |
| IP | IP65 |
| IK | IK10 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| ETL | No |
| Fire Rated (BS 476 PT21 compliant) | No |
| Induction | No |
| Emergency mode | No |
| Motion sensor | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | No |
| Resin potting | No |
| Type of light emission | Double emission |
| Net weight | 16.550 Kg |

| Finishing diffuser | |
|--------------------|---------|
| Material | PE |
| Colour | neutral |

Ceiling Lights | 220-240 V | 1xE27
15189

Double emission ceiling lights for outdoor application. Compatibility: LED lamp, halogen 77 W, compact fluo 30 W; lamp cap 1xE27.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 16.550 kg.

The device features protection class II and can be ceiling-mounted.

| Illuminotechnical Features | |
|-----------------------------|-------------|
| Light Output Ratio (LOR) | 77 % |
| Luminous flux (source) | 1320 lm |
| Luminaire luminous flux | 1480 lm |
| Consumption | 30 W |
| Luminaire efficacy | 63 lm/W |
| Colour rendering index | 100 Ra |
| OPTICAL | |
| Light distribution simmetry | Symmetrical |
| C0/C180 optics | 180° |

