



Ceiling Lights | 220-240 V | 2xE27
71642



Technical data	
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Lamp cap	2 x E27 Max 46W
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	frontal
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Induction	No
Emergency mode	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Double emission
Net weight	2.595 Kg

Finishing diffuser	
Material	Glass
Colour	white
Processing	Silk-screening



Ceiling Lights | 220-240 V | 2xE27
71642

Double emission ceiling lights for indoor application. Compatibility: LED lamp, compact fluo 14 W, halogen 46 W; lamp cap 2xE27.

The diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.595 kg.

The device features protection class I and can be wall lights or ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	1400 lm
Colour temperature	2500 K
Colour rendering index	100 Ra